

Product Specification AnGus^{1516®}

Description:	Powder product for brewing liquor preparation during mashing
Appearance:	free flowing powder
Colour:	white-greyish

Analysis:

Moisture:	max. 5 %
pH value (1 g/100 mL water):	8.5 – 9.5
Bulk density:	300 - 400 g/L

Values for information purposes:

Soluble in potassium hydrogen phthalate buffer (MEBAK, Volume IV):

Calcium (Ca):	max.	50 g/kg
Magnesium (Mg):	max.	2 g/kg
Iron (Fe):	max.	2 mg/kg
Lead (Pb):	max.	5 ppm
Arsenic (As):	max.	2 ppm
Total heavy metals (as Pb):	max.	10 ppm

The use of AnGus^{1516®} is in conformance with the requirements of the German purity law for the recommended application. All ingredients of AnGus^{1516®} are permitted according to European law for the use in feedstuffs. Therefore brewers' grains and yeast deposits can be used in animal feed also after the application of AnGus^{1516®}.

ERBSLÖH Geisenheim AG Erbslöhstraße 1, 65366 Geisenheim, Germany Tel: +49 6722 708-0, Fax: +49 6722 6098, info@erbsloeh.com, www.erbsloeh.com

version 001 - 12/2012 MM - printed on: 12.02.2015